

THE
outdoor
ALCHEMIST
—
corradi.eu



Bioclimatic
Imago

Corradi
OUTDOOR LIVING SPACE



COLORI | COLORS | COLORIS | FARBEN | COLORES | KLEUREN

Struttura (interno/esterno) e lamelle | Structure (inside/outside) and blades | Structure (interne/externe) et les lames
Struktur (innen/außen) und lamellen | Estructura (interno/externo) y lamas | Structuur (in/uit) en lamellen



	DIMENSIONI MASSIME MODULO SINGOLO MAXIMUM DIMENSIONSSINGLE MODULE DIMENSIONS MAX. MODULE UNIQUE MAX. ABMESSUNGEN EINZELNES MODUL DIMENSIONES MÁXIMAS MÓDULO INDIVIDUAL MAX. AFMETINGEN ENKELE MODULE (span x pivot cm)						
	500 x 627	—	●	Opt	Opt	Opt	Opt

		a lamelle chiuse with closed blades avec lames fermées mit geschlossenen Lamellen con lamas cerrada bij gesloten lamellen	a lamelle aperte with open blades avec lames ouvertes mit offenen Lamellen con lamas abiertas bij open lamellen
	class EN 13561 500 x 627 (span x pivot cm)	6	3

SEZIONE PILASTRI | PILLAR SECTION | SECTION DE PILIER | QUERSCHNITT DER PFOSTEN
SECCIÓN DE COLUMNA | DOORSNEDE STAANDERS

15 x 15 cm

SEZIONE TRAVE | BEAM SECTION | SECTION DE LA POUTRE
STÜTZBALKEN | SECCIÓN DE LA VIGA | DRAAGBALKGEDEELTE

25 x 15 cm

PASSO LAME | BLADE PASSAGE | L'ÉTAPE DES LAMELLES | LAMELLENABSTAND
PASO DE LA LAMA | AFSTAND TUSSEN LAMELLEN

21,5 cm


GRONDE INTEGRATE (SPAN & PIVOT) | INTEGRATED GUTTERS (SPAN & PIVOT) | GOUTTIÈRES INTÉGRÉES (SPAN & PIVOT)
INTEGRIERTE RINNEN (SPAN & PIVOT) | CANALONES INTEGRADOS (SPAN & PIVOT) | GEÏNTEGREERDE DAKGOTEN (SPAN & PIVOT)




RESISTENZA ALLA PIOGGIA | WATER RESISTANCE | RESISTANCE A LA PLUIE
REGENBESTÄNDIGHEIT | RESISTENCIA A LA LLUVIA | REGEN BESTENDIGHEID

5400 l/h


2 scarichi aperti | 2 drains open | 2 écoulements ouverts
2 offene Abflüsse | 2 desagües abiertos | 2 open afvoeren



MONOCHROME



BICOLOR CLASSIC



BICOLOR COCOON

